

ADT: Jump Form Version 1.0

Requirements Specification

Author	Janet
Version	1.0
Printed	2001-10-22 1:01 PM

Document Revisions

Revisions on this document should be recorded in the table below:

	Date	Description	Author
1	10 September 2001	First Draft	Janet
2	10 September 2001	First Edit	Josh
3	12 October 2001	Screenshots, Params, Editing, Views	Josh
4			

TABLE OF CONTENTS

1 Introduction	4	
1.1 Purpose of this document		4
1.2 Scope of this document		4
1.3 Overview		4
1.4 Business Context		4
2 General Description	4	
2.1 Product Functions		4
2.2 General Constraints		4
3 Functional Requirements	9	
3.1 Jump Form Application		9
3.1.1 <i>Description</i>		9
3.1.2 <i>Risks and Dependencies</i>		13
4 Database Design	14	
4.1 Description		14
4.2 Communications Interfaces		14
5 Other non-functional attributes	14	
5.1 Reliability		14
5.2 Maintainability		14
5.3 Portability		14
5.4 Extensibility		14
5.5 Reusability		14
5.6 Serviceability		14

1 Introduction

1.1 Purpose of this document

The purpose of this document is to specify the functional and system specification of the Jump Form application. This document provides a road-map through which the implementation of the application will be developed and, where applicable, will also contain information detailing technical design constraints and assumptions.

1.2 Scope of this document

The specification covers the functional specifications of the Jump Form application. This specification does not extend to third party or infrastructure components (such as a web server installation and/or configuration).

1.3 Overview

The basic requirements summary build-in for the Jump Form application:

- To allow logged on users to go to the selected website links.

1.4 Business Context

Jump Form is an application designed for multiple users over a wide area. The generic version is open source for distribution. Anyone may take advantage of the powerful eXtropa Perl ADT. Improvements will be made incrementally as bug reports come in and suggestions are made. The generic Jump Form will ultimately benefit both the company and our users.

2 General Description

2.1 Product Functions

The general function of the Jump Form application allows users to access the selected website links. The application generates a dynamic page depending on the entered information and the setup preferences.

2.2 General Constraints

Users must log in before they can use the application. The application will be written in Perl and the data files are stored in a common flat file system (ASCII File). This will slow down in terms of searching for information if there is a presence of huge database.

The application is also able to interface with relational databases should the administrator desire it.

Bold Params indicate Section Headings. *Italic Params* are objects.

Indented Params are configurable variables.

Grayed out or missing items are not required or not available in the default configuration.

Param	Default configuration	Notes
Language	Perl	
Session Setup		
Type	File	Note that flatfile data sources are slow. We recommend upgrading to a database based data source
Max Modify Time	1 hour	
Fatal Timeout	Off	
Fatal if session not found	Off	
<i>Session Manager Setup</i>		
Type	FormVar	
Cgi Object	\$CGI	
Session Params	Session Config Params	
Authentication Setup		For the datasource
Type	File	
Field Delimeter	(pipe)	
Create a file if none exists	On	
Field Names	From Auth User Datasource	
File	Scriptname.users.dat	Path is set at start of script
Default Authentication Fields	Username, password, groups, firstname, lastname, email	
Authentication Manager Setup		How requests are processed
Color for even rows	E5E5E5	
Color for Odd Rows	FFFFFF	
CSS View URL	\$CSS_VIEW_URL	
Application Logo	logo.gif	
Application Logo Height	40	
Application Logo Width	353	
Application Logo ALT	WebDB Demo	
HTTP Header Params	[-EXPIRES => '-1d']	
Document Root URL	'/' or web root directory	
Image Root URL	/Images/Extropa	
Script Display Name	'Jump Form'	
Script Name	\$CGI->script_name()	
Page Top View	PageTopView	
Page Bottom View	PageBottomView	
Link Target	'_self' or current window	
<i>User_Fields</i>	Auth_username, auth_password, auth_groups, auth_firstname, auth_lastname, auth_email	
<i>Mail Params</i>		
Type	Sendmail	Default on most systems
<i>User Mail Send Params</i>		
From	you@yourdomain.com	

Subject	Password Generated	
<i>Admin Mail Send Params</i>		
From	you@yourdomain.com	
To	you@yourdomain.com	
Subject	Registration Notification	
<i>Auth Manager Config Params</i>		
Type	CGI	
Allow Registration	On	
Allow User Search	On	Allow anyone to check for an old account.
Generate Password	Off	
Default Groups	Normal	
Email Registration to Admin	Off	
Display Registration After Failure	On	
Data Handler Setup		How data is handled
<i>Add Form DHM Config</i>		
Type	CGI	
CGI Object	\$CGI	
Data Handlers	Email, Exists, HTML, String	
Field Mappings	Record_id, url	
Datasource Setup		Configure the database and fields displayed
Field Names	record_id, url	Corresponds to default extropa database
<i>Sample Default Widget Definitions</i>		
Display Name	Country	Name that appears in the browser
Type	Textfield, textarea, popup_menu	
Name	Fname	Internal field name
Size	30	Display size in characters
Maxlength	80	Maximum number of characters permitted
Rows	6	Initial height of textarea
Cols	30	Initial width of textarea
Wrap	VIRTUAL	Wrapping of text in textarea
<i>Basic Datasource Config Params</i>		
Type	File	
File	\$APP_DATAFILES_DIRECTORY/\$APP_NAME.dat	
Field Delimiter	(pipe)	
Comment Prefix	#	Ignore lines starting with #
Create File if None Exists	On	
Field Names	\@DATASOURCE_FIELD_NAMES	
Key Fields	['record_id']	Not required if key is not used
Field Types	Record_id => 'Autoincrement'	Specify a specific kind of field

Logging Setup		
Type	File	
Log File	\$APP_DATAFILES_DIRECTORY/\$APP_NAME.log	
Log Entry Suffix	' ' . _generateEnvVarsString() . ' ',	
Log Entry Prefix	'JumpForm '	
View Setup		
		Views to use, display, and defaults
<i>Valid Views</i>	CSSView, SimpleForm/FormView, JumpView, LogoffView	The program cannot display views that are not available here.
<i>View Display Params</i>		Defaults for Views
Application Logo	logo.gif	
Application Logo Height	40	
Application Logo Width	353	
Application Logo ALT	WebDB Demo	
Color for Even Rows	E5E5E5	
Color for Odd Rows	FFFFFF	
Display Fields		
Table BG Color 1	6699CC	
Table BG Color 2	E5E5E5	
Table BG Font Color1	BLACK	
Table BG Font Color2	BLACK	
Filter Setup		
<i>HTMLIZE Filter</i>		
Type	HTMLize	
Convert Double Linebreak to P	On	
Convert Linebreak to BR	On	
<i>Charset Filter</i>		
Type	CharSet	
<i>Embed Filter</i>		
Type	Embed	
Enable	Off	
Action/Workflow Setup		
<i>Action Handler List</i>	Defaults	User should not need to modify
<i>Action Handler Action Params</i>		
Action Handler List	\@ACTION_HANDLER_LIST	
Add Acknowledgment View Name	AddAcknowledgementView	
Add Email Body View	AddEventEmailView	
Add Form View Name	AddRecordView	
Allow Additions Flag	On	
Allow Username Fields to be Searched	On	
Allow Modifications Flag	On	
Application Sub Menu View Name	ApplicationSubMenuView	
Options Form View Name	OptionsView	

Auth Manager Config Params	\@AUTH_MANAGER_CONFIG_PARAMS	
Add Record Confirmation View Name	AddRecordConfirmationView	
Basic Data View Name	BasicDataView	
CGI Object	\$CGI	
CSS View URL	\$CSS_VIEW_URL	For speed, change CSS URL to a location outside the CGI directory.
CSS View Name	CSSView	
Datasource Config Params	\@DATASOURCE_CONFIG_PARAMS	
Delete Acknowledgment View	DeleteAcknowledgementView	
Delete Record Confirm View	DeleteRecordConfirmationView	
Records Per Page Options	[5, 10, 25, 50, 100]	Remove or change numbers as desired. This appears under Options.
Max Records Per Page	\$CGI->param('records_per_page') 5	
Sort Field 1	\$CGI->param('sort_field1') 'category'	Sort by which field?
Sort Field 2	\$CGI->param('sort_field2') 'fname'	Sort by which field?
Sort Direction	\$CGI->param('sort_direction') 'ASC'	ASC=Ascending, DSC=Descending
Delete Form View Name	BasicDataView	
Delete Email Body View	DeleteEventEmailView	
Details View Name	DetailsRecordView	
Data Handler Manager Config Param	\@DATA_HANDLER_MANAGER_CONFIG_PARAMS	
Hidden Admin Fields View	HiddenAdminFieldsView	
Input Widget Definitions	\@INPUT_WIDGET_DEFINITIONS	
Key Field	record_id	
Logoff View	LogoffView	
URL Encoded Admin Fields View	URLEncodedAdminFieldsView	
Log Config Params	ModifyAcknowledgementView	
Modify Acknowledgment View	ModifyRecordConfirmationView	
Mail Config Params	\@MAIL_CONFIG_PARAMS	
Modify Form View	ModifyRecordView	
Modify Email Body View	ModifyEventEmailView	
Power Search View	PowerSearchFormView	
Require Auth for Details	Off	Is authorization required for the action?
Send Email on Delete	Off	
Send Email on Modify	Off	
Send Email on Add	Off	

Session Object	\$SESSION	
Session Timeout View	SessionTimeoutErrorView	
Templates Cache Directory	\$TEMPLATES_CACHE_DIRECTORY	
Valid Views	\@VALID_VIEWS	
View Display Params	\@VIEW_DISPLAY_PARAMS	
View Filters Config Params	\@VIEW_FILTERS_CONFIG_PARAMS	
View Loader	\$VIEW_LOADER	
Simple Search String	\$CGI->param('simple_search_string') ""	
First Record on Page	\$CGI->param('first_record_to_display') 0	
Last Record on Page	\$CGI->param('first_record_to_display') "0"	
Page Top View	PageTopView	
Page Bottom View	PageBottomView	
Action Handler Plugins	;%ACTION_HANDLER_PLUGINS,	

3 Functional Requirements

3.1 Jump Form Application

3.1.1 Description

The following definitions only cover the Default settings and views.

Authentication Definition Views

The application will allow any user read-only rights to view the records registered in the application. Only registered users however, may add, modify, and delete records. There is no capacity for multiple group definitions, thus the default group is "Normal" and cannot be changed.

Default Settings Permit:


- Any user may view the database
- Any user may search the database
- Registered users may add, modify, and delete records
- Registration is available to anyone

Registration of normal users is simply done by pressing "Logon" and following the Registration Views. User data is written to the datasource. In the default installation, it is written to `Datafiles/JumpForm/jump_form.users.dat`. It is recommended that administrators do not alter the contents, especially the encrypted passwords. The information is listed as:


```
username | password | group_name | fname | lname | email
```

Registration of Administrative users may be done at a later date. System administrators will be able to alter hard data in databases or flat files as needed.


- **Logon View** requests the Username and Password of registered users. Users may attempt to logon, Register, or Search for Account. Also the view for failed logins.




- **Register View** permits any user to enter Username, Password, Confirm, Password, First Name, Last Name, and E-Mail. The user may then Register or Return to Logon Screen.




- **Register Confirmation View** confirms registration and returns the user to the Logon View.




- **Search for Account** requests an email address to match users and then sends the password to the user.




- **Search for Account Users Found** displays the username that matches the email address given.



- **Search for Users No Results** appears when no email address is associated with a username.




- **Logoff View** logs the user out and confirms the logoff. The session is terminated.



Application Specific View Definitions

- **Jump Form** has a popup box with the available links.



3.1.2 Risks and Dependencies

4 Database Design

4.1 Description

The data of the application will be stored in a flat file. Each data fields of a record will be separated by '|'.

Field Name	Description
record_id	Record value (Auto Incremental Value)
url	Website URL that is accessed by the users.

4.2 Communications Interfaces

5 Other non-functional attributes

5.1 Reliability

Highly reliable in a properly secured environment.

5.2 Maintainability

Requires little maintenance. Owners will want to clear out a large flatfile now and then as well as ensure their installation is secure from hackers. Users of relational databases will probably not need to clear out their database.

5.3 Portability

5.4 Extensibility

Information entered is portable to any relational database. The program can easily be switched to a new database with just a few lines of code. The program relies on the eXtropa ADT that divorces form and function.

5.5 Reusability

Jump Form is highly reusable. The application can be modified for just about anything!

5.6 Serviceability